

Principais Caraterísticas

- > Programação semanal;
- > Termostato ambiente;
- > Funcionamento automático;
- > Display com controlo digital;
- > Pés reguláveis;
- > Carregamento de pellets através da conduta com posição frontal ou lateral.



Recuperador de calor de pellets para aquecimento a ar.

Desenho inovador.

Com uma potência nominal de 10,5 kW, ideal para a sua sala, tornando-a mais eficiente e económica.

Carregamento de pellets através da conduta com posição frontal ou lateral.

Obs.: após a boa receção do equipamento pelo cliente, o vidro fica excluído de garantia.

Código	Modelo
0601-0187	Recuperador de Pellets a Ar MORFEU
1705-0188	Suporte para Recuperador de Pellets a Ar

Technical drawings of the Forno 3000 oven, showing dimensions in millimeters (mm).

Front View: Dimensions: 796 mm (width), 580 mm (height), 706 mm (height to top of door).

Side View: Dimensions: 584 mm (width), 610 mm (width to side panel), 109,5 mm (depth).

Top View: Dimensions: 368 mm (width), 345 mm (height), 116 mm (height to top of door).

Rear View: Dimensions: 745 mm (width), 122 mm (width to side panel), 121 mm (width to side panel), 53 mm (height to bottom of door), 93,5 mm (height to top of door), 273,1 mm (width to side panel), 1 mm (width to side panel).

Isometric View: Shows the oven with its door open, highlighting the internal components and the air intake (2) and exhaust (4) ports.

LEGENDA:

- 1 - Tomada de Alimentação
- 2 - Entrada de Ar
- 3 - Saída de Fumos
- 4 - Saída de Ar Canalizada

1 - Tomada de Alimentação
2 - Entrada de Ar
3 - Saída de Fumos
4 - Saída de Ar Canalizável

Componentes



DADOS TÉCNICOS	MORFEU
Potência Térmica Mínima / Máxima (kW)	4 / 10,5
Potência Térmica Convecção e Radiação Mínima / Máxima (kW)	3,8 / 9,3
Rendimento Mínimo / Máximo (%)	88,5 / 93,2
Volume Aquecido Mínima / Máxima (m³)	90 / 290
Consumo Horário Mínima / Máxima (kg/h)	0,82 / 2,14
Alimentação (V/Hz)	230/50
Consumo Elétrico Nominal (W)	153
Capacidade do Depósito (kg)	19
Tiragem Mínima da Chaminé (Pa)	10
Tubo de Tomada de Ar (mm)	40x60 (Rectangular)
Saída de Fumos (mm)	80
Peso (kg)	122
Combustível	Pellet Ø6mm
Garantia	2 Anos

