


JMT1 MÓDULO RECTO 1 M
 STRAIGHT PIPE 1 M


Øint	80	100	130
Øext	125	150	200
L útil	950	950	950
A	35	35	35


JMT0 MÓDULO RECTO 0,5 M
 STRAIGHT PIPE 0,5 M


Øint	80	100	130
Øext	125	150	200
L útil	450	450	450


JMTP MÓDULO RECTO 0,25 M
 STRAIGHT PIPE 0,25 M


Øint	80	100	130
Øext	125	150	200
L útil	200	200	200


JMEG MÓDULO EXTENSIBLE 0,25 A 0,40 M
 MÓDULO EXTENSIBLE 0,25 A 0,40 M


Øint	80	100	130
Øext	125	150	200
L min	250	250	250
L max	400	400	400


JMCC CODO DE 45°
 ELBOW 45°


Øint	80	100	130
Øext	125	150	200
X	54	57	65
Y	120	126	146


JMCC CODO DE 90°
 ELBOW 90°


Øint	80	100	130
Øext	125	150	200
X	138	149	173
Y	135	147	172




JMTN	TE 90° TEE 90°		
Øint	80	100	130
Øext	125	150	200
L útil	245	270	330
B	123	135	165
C	108	120	145




JMTB	TE COAXIAL HUMOS HEMBRA TEE COAXIAL FLUE FEMALE BRANCH		
Øint	80	100	130
Øext	125	150	200
L útil	200	200	-
B	118	100	-
C	120	132	-




JMTD	TE COAXIAL HUMOS MACHO TEE COAXIAL FLUE MALE BRANCH		
Øint	80	100	130
Øext	125	150	200
L útil	200	200	-
B	118	100	-
C	120	132	-




JMTC	TE COAXIAL ENTRADA AIRE TEE COAXIAL AIR ENTRY		
Øint	80	100	130
Øext	125	150	200
L útil	200	200	-
B	100	118	-
C	113	125	-




JMTA	TAPA COAXIAL LID		
Øint	80	100	130
Øext	125	150	200
B	40	40	40




JMTV	TERMINAL SALIDA VERTICAL 1 M PIPE WITH VERTICAL OUTSIDE 1 M		
Øint	80	100	130
Øext	125	150	200
L útil	945	945	945



JMTX	TERMINAL SALIDA VERTICAL 0,28 M PIPE WITH VERTICAL OUTSIDE 0,28 M		
Øint	80	100	130
Øext	125	150	200
L útil	195	195	230


JMTH **TERMINAL SALIDA HORIZONTAL 1 M**
PIPE WITH HORIZONTAL OUTSIDE 1 M


∅int	80	100	130
∅ext	125	150	200
L útil	955	955	955


JMAM **AMPLIACIÓN**
INCREASER


∅A	80/125	100/150	-
∅B	100/150	130/200	-
L útil	175	175	-


JMAD **ADAPTADOR A CALDERA**
BOILER ADAPTOR


∅A	80/125	100/150	130/200
∅B	80/125	100/150	130/200
L útil	150	150	150


JMSB **SOPORTE BASE REGULABLE 50 A 80 MM**
ADJUSTABLE BASE SUPPORT 50 TO 80 MM


∅A	80	100	130
∅B	125	150	200
L útil	200	200	200
Bmin.	50	50	50
Bmax.	80	80	80


HISA **SOPORTE MURAL REGULABLE 50 A 80 MM**
ADJUSTABLE WALL SUPPORT 50 TO 80 MM


∅nom	125	150	200
Amin.	50	50	50
Amax.	80	80	80
B	30	30	40


HISF **SOPORTE FORJADO**
JOIST SUPPORT


∅nom	125	150	200
A	150	150	150
B	30	30	40


HIPN **TAPAJUNTAS INOX. REDONDO**
ROUND INOX ROSETTE

∅nom	125	150	200
∅A	120	120	120
∅B	374	399	475



HITJ **TAPAJUNTAS**
WALL JOINT ROSETTE

∅nom	125	150	200
A	40	40	40
B	15	15	15




HICU CUBRE-AGUAS ADAPTABLE 0 A 35°
 ADJUSTABLE FLASHING 0 TO 35°

Ønom	125	150	200
A	610	640	700
B	150	175	225
C	150	160	180



HICS CUBREAGUAS DE PLOMO 20°- 45°
 LEAD FLASHING 20°- 45°

Ønom	125	150	200
A	751	786	855
B	650	675	725
C	135	160	210



HILL COLLARÍN ANTILLUVIA
 COLLAR

Ønom	125	150	200
Øext	200	225	300
Øint	126	151	201
A	75	75	100